



cerámica

**CERPA, S.L.**

revestimientos cerámicos y gres

OFICINAS - EXPOSICIÓN - FACTORÍA

Carretera de Burriana, 28 - Apt./Box 85

12200 ONDA (Castellón) España

Tel. 964 60 16 51 - Fax 964 60 45 94

<http://www.cerpa.com>


VAT CEE: ES B-12027983

## TECHNICAL CHARACTERISTICS SHEET

REFERENCE	<b>60 X 60 MATT SERIES</b> 58,5 X 58,5 RECTIFIED 60 X 60 NO RECTIFIED DRY PRESSED GLAZED FLOOR TILE GROUP: Bib
-----------	--

TESTS PERFORMED	RESULTS
UNE-EN ISO 10545-2 DIMENSIONS AND SURFACE QUALITY	CONFORMS TO STANDARD
UNE-EN ISO 10545-3 WATER ABSORTION 0,5<E<3%	AVERAGE VALUE 0,9%
UNE-EN ISO 10545-4 MODULUS OF RUPTURE	MODULUS OF RUPTURE (N/mm <sup>2</sup> ) 40 BREAKING STRENGHT (N) 1657
UNE-EN ISO 10545-7 RESISTANCE TO SURFACE ABRASION PEI	CLASS 4
UNE-EN ISO 10545-5 LINEAR THERMAL EXPANSION	6,4 x 10 <sup>-6</sup> /°C
UNE-EN ISO 10545-9 THERMAL SHOCK	RESIST
UNE-EN ISO 10545-13 CHEMICAL RESISTANCE	AMMONIUM CHLORIDE GA SODIUM HYPOCHLORITE GA
UNE-EN ISO 10545-14 RESISTANCE TO STAINS	GREEN STAINING AGENT IN LIGHT OIL CLASS 5 IODINE ALCOHOL SOLUTION CLASS 5 OLIVE OIL CLASS 5
UNE-EN 67101 and 1M SCRATCH HARDNESS	Mohs 6 - 8

Date. 01/02/16



Cerpa, S.L. Laboratory